

# SAFETY DATA SHEET

This SDS complies with REACH 1907/2006 and 2001/58/EC, GHS, OSHA 29CFR 1910.1200

## Section 1: Chemical Product and Company Identification

MANUFACTURER'S NAME  
 Advantage Coatings Technology  
 1533 Arthur Avenue  
 Unit B  
 Louisville, Colorado 80027-3054

EMERGENCY TELEPHONE  
 Chemtrec U.S.-Canada: 800-424-9300  
 Chemtrec International: 703-527-3887  
 Information: 303-499-1310  
 Fax: 720-536-8365

Safety Data Sheet Competent Person: Kevin Durling

info@actfinish.com

DATE PREPARED: May 6, 2015

**REVISION DATE: May 27, 2015**

PRODUCT NAME: **GAME LINE PAINT**  
 FORMULA: Preparation/Mixture  
 PRODUCT USE: Hardwood floor finish

## Section 2: Hazards Identification

**GHS Hazard Class**

Signal word:

Hazard Statement:

Flammable Liquid -- Category 3

Warning

H226



Flammable liquid and vapor

Precautionary Statements:

Prevention

P210

Keep away from heat, sparks, and open flames – NO smoking.

P233

Keep container tightly closed.

P240

Ground/bond container and receiving equipment.

P241

Use explosion proof electrical/ventilating/lighting equipment.

P242

Use only non-sparking tools.

P243

Take action to prevent static discharges.

P260

Avoid breathing dust/fuel/gas/mist/vapors/spray.

P280

Wear protective gloves/protective clothing/eye protection/face protection.

Response

P370-P378

In case of fire, use foam, dry chemical, or carbon dioxide.

P303+P361+P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing.

P403+P235

Rinse skin with water/shower.

Storage

P403+P235

Store upright in a well-ventilated place. Keep cool.

P405

Store locked up.

Disposal

P501

Waste from Residues and Unused Products: Follow the waste disposal requirements of your country, state, or local authorities.

Hazard(s) Not Otherwise Classified (HNOC): Not classified

HAZARD CLASSIFICATION:

Classified as hazardous based on IATA, IMDG, and DOT.

FIRE AND EXPLOSION:

Considered flammable or combustible.

Product emits toxic fumes when burned.

POTENTIAL HEALTH EFFECTS:

<1 % of mixture consists of ingredients of unknown acute toxicity

APPEARANCE:

Amber liquid

NFPA Rating:

Component	Health (Blue)	Flammability (Red)	Reactivity (Yellow)	Special (White)
Game Line Paint	0	2	0	----

### Section 3: Composition, Information on Ingredients

PRODUCT COMPOSITION	APPRX %	CAS NO.	CANADA DSL	TSCA	AUSTRALIA (AICS)
Resin 1	20 - 30	N/A	Y	Y	Y
Stoddard Solvent	<60	8052-41-3	Y	Y	Y
Resin 2	2.5-7.5	TS	N	Y	N
Filler 1	20-30	TS	Y	Y	Y
Filler 2	<3	TS	Y	Y	Y

COLOR PIGMENT(S) COMPOSITION	CAS NO.	
Naphtha (Petroleum) hydrotreated heavy	64742-48-9	X
Distillates (petroleum), hydrotreated light	64742-47-8	X
2-butanone oxime	96-29-7	X
Isotridecylalcohol, ethoxylated, phosphate compound with N,N-dimethylcyclohexanamine	164383-18-0	X
Titanium Dioxide	13463-67-7	X
Alcohol ethoxylate phosphate ester	73038-25-2	X
2-methoxy-1-methylethyl acetate	108-65-6	X
N-butyl acetate	123-86-4	X
Carbon black	1333-86-4	X
Polymeric Alkoxyate	TS	X

Trade Secret (TS) Some items on this SDS may be designated as trade secrets. Bonafide requests for disclosure of trade secret information to medical personnel must be made in accordance with the provisions contained in 29 CFR 1910.1200 I 1-13.

### Section 4: First Aid Measures

#### Description of First Aid Measures:

INHALATION:	Remove to fresh air. If not breathing, provide CPR (cardio pulmonary resuscitation). Get immediate medical attention.
SKIN CONTACT:	Immediately flush skin with plenty of soap and water for at least 15 minutes. Remove contaminated clothing.
EYE CONTACT:	Immediately flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention.
INGESTION:	If swallowed do not induce vomiting, give large quantities of water to drink. Never give anything to an unconscious person. Get immediate medical attention.

#### Most important symptoms and effects, both acute and delayed

Symptoms/Injuries After Ingestion	Ingestion (swallowing) may irritate the mouth, throat and stomach. Aspiration into lungs may cause chemical pneumonia and lung damage. Ingestion is not an anticipated route of exposure for this material in industrial use.
Symptoms/Injuries After Inhalation	Inhalation of vapors in high concentration may cause irritation of respiratory system. Inhalation of high vapor concentrations can cause CNS-depression and narcosis.
Symptoms/Injuries After Skin Contact	May cause skin irritation. Symptoms may include redness, drying, defatting, and cracking.
Symptoms/Injuries After Eye Contact	Eye irritation may result.

Chronic Effects: Exposure to organic solvents during pregnancy may cause an increased risk of birth defects.



## Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately.

## Section 5: Fire-fighting Measures

### Suitable extinguishing media

Use foam, dry chemical, or carbon dioxide.

### Special hazards arising from the substance or mixture

No data available.

### Protective actions fire-fighters

Wear self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing. Thoroughly decontaminate all protective equipment after use. Evacuate all persons from the fire area to a safe location. Move non-burning material, as feasible, to a safe location as soon as possible. Fire fighters should be protected from potential explosion hazard while extinguishing the blaze. DO NOT extinguish a fire resulting from the flow of this combustible liquid until the flow of liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished. Use water spray to cool fire-exposed containers.

### Further information

Combustible material. Vapors may form explosive mixtures with air.

Flash back possible over considerable distance. When driers such as cobalt naphthanate are added, air oxidation of the resin or materials contaminated with the resin may cause it to spontaneously combust. To avoid spontaneous combustion: (1) prevent residue build-up and (2) soak soiled rags, spraybooth filters and over-spray waste in a closed water-filled metal container. Closed containers may rupture when exposed to extreme heat. Empty containers may retain product residue (liquid and/or vapor). Do not pressurize, cut, weld, braze, solder, drill, grind, or expose these containers to heat, flame, sparks, static electricity, or other sources of ignition as the container may explode and may cause injury or death.

## Section 6: Accidental Release Measures

### Personal precautions, protective equipment, and emergency procedures

Wear proper personal protective equipment. Avoid breathing vapors or mist.

### Environmental precautions

Prevent further leakage or spillage if safe to do so.  
Prevent spills or contaminated rinse water from entering sewers or watercourses.

### Methods and materials for containment and cleaning up

In case of small spills, absorb with inert materials such as earth or dry sand. Place in a chemical waste container.  
In case of large spills, dike the spill, if possible. Call emergency services. Absorb the chemical.  
Warn other workers of spill and contain spill.  
Recover spill by using absorbent and sweeping up waste material.  
In case of large spills, dike the spill, if possible. Call emergency services.  
Place material into a chemical waste container.  
Eliminate all sources of ignition and ventilate area.

**Reference to other Sections** For personal protection reference section 8. For disposal reference section 13.

## Section 7: Handling and Storage

### Precautions for safe handling

For best results store upright between 12 – 25 °C (50 – 80 °F).  
Avoid freezing.  
Keep container closed when not in use.  
Wear proper protective equipment and avoid contact with skin, eyes, or clothing.  
Wash hands after handling this material.  
Follow all applicable local regulations for handling and storage.  
Utilize chemical segregation.

### Conditions for safe storage, including any incompatibilities

Keep away from heat and flame.  
Take precautionary measures against static discharge.



Keep away from heat, sparks, flame, direct sunlight and other possible sources of ignition.  
 Use only with adequate ventilation.  
 Do not inhale vapors.  
 Avoid spilling and releasing vapor.

**Specific uses**

This product is a hardwood floor finish.

**Section 8: Exposure Controls/Personal Protection**

**Control Parameters:**

PRODUCT COMPOSITION	ACGIH TLV	OSHA PEL	NIOSH REL	U.S. WEEL TWA	Canada OEL
Stoddard Solvent	100 ppm	2900 mg/m <sup>3</sup> 500 ppm	20000 mg/m <sup>3</sup> IDLH	-----	2900 mg/m <sup>3</sup> 500 ppm
Calcium Carbonate	**PNOS	*PNOR	10 mg/m <sup>3</sup> Total Dust, 5 mg/m <sup>3</sup> Respirable dust	-----	-----

\*PNOR (Particulates Not Otherwise Regulated): OSHA 5 mg/m<sup>3</sup> Respirable fraction (R), 15 mg/m<sup>3</sup> Total Particulates

\*\*PNOS (Particulates Not Otherwise Specified): ACGIH 3 mg/m<sup>3</sup> Respirable fraction (R), 10 mg/m<sup>3</sup> Total Particulates, total dust less than 1% quartz.

**Exposure controls**

VENTILATION:

Always provide good general, mechanical room ventilation where this chemical/material is used.

SPECIAL VENTILATION CONTROLS:

Use this material inside totally enclosed equipment, or use it with local exhaust ventilation at points where vapors can be released into the workspace air.

RESPIRATORY PROTECTION:

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or the CEN European Standards (EU). Use a NIOSH/MSHA or European Standard (EN) approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

PROTECTIVE GLOVES:

Neoprene, butyl, or nitrile rubber gloves are recommended.

EYE PROTECTION:

Recommend eye protection using safety glasses or goggles.

SKIN PROTECTION:

Suitable protective clothing to prevent skin contact

WORK/HYGIENE PRACTICES:

Avoid breathing vapor. Avoid contact with eyes. Wash hands after handling.

EXPOSURE LIMITS

Reference Section 2

OTHER EQUIPMENT:

Make safety shower, eyewash stations, and hand washing equipment available in the work area.

**Section 9: Physical and Chemical Properties**

	PRODUCT CRITERIA
APPEARANCE - COLOR:	Pigmented
PHYSICAL STATE:	Liquid
ODOR:	Slight Solvent Odor
ODOR THRESHOLD	Not Available for product
PH	Not Available for product
MELTING POINT/FREEZING POINT:	<-75 °C (-103 °F) Stoddard solvent
INITIAL BOILING POINT AND BOILING RANGE:	161-198 °C
FLASH POINT:	40 °C (104 °F) Seta closed cup)
EVAPORATION RATE:	0.18 (BuAc = 1) Stoddard solvent
FLAMMABILITY (Solid, gas)	Not Available for product
UPPER/LOWER FLAMMABILITY OR EXPLOSIVE LIMITS	Not Measured



VAPOR PRESSURE	0.27 kPa @ 20 °C Stoddard solvent
VAPOR DENSITY (AIR = 1)	4.9 (Air = 1) Stoddard Solvent
RELATIVE DENSITY (@25 °C):	0.899—0.922 @ 25 °C
SOLUBILITY(IES)	Not applicable for product
OXIDIZING PROPERTIES	Not Available for product
PARTITION COEFFICIENT: n-octanol/water	Not Available for product
AUTO IGNITION TEMPERATURE	260 °C Stoddard solvent
DECOMPOSITION TEMPERATURE	Not Available for product
VISCOSITY	Not Available for product
VOC CONTENT	<420 g/l

## Section 10: Stability and Reactivity

Reactivity:	Not reactive.
Chemical Stability:	Stable under normal conditions.
Possibility of Hazardous Reactions:	Will not occur
Conditions to Avoid:	Avoid heat, sparks, open flames and other ignition sources.
Incompatibility (Materials to Avoid):	Strong oxidizers.
Hazardous Decomposition Products:	Hazardous decomposition products are not expected to form during normal storage.

## Section 11: Toxicological Information

There is no toxicological information available for the product mixture.

GHS Required Criteria	Toxicity Criteria	Toxicity Information	Comments	Chemical Constituent
Acute Toxicity	LD50 Oral Rat	>5000 mg/kg		Stoddard Solvent
	LD50 Dermal Rabbit	>3150 mg/kg		Stoddard Solvent
	LC50 Rat	>6.1 mg/kg		Stoddard Solvent
	LD50 Oral Rat	6450 mg/kg		Calcium Carbonate
Skin Corrosion/Irritation	Dermatitis in rabbits	2 g/kg	4 weeks	Stoddard Solvent
Serious Eye Damage / Eye Irritation		No information is available.		
Respiratory or Skin Sensitization		No information is available.		
Germ Cell Mutagenicity		No information is available.		
Carcinogenicity		Not listed	NTP	
		Not listed	IARC	
		Not listed	OSHA	
Reproductive Toxicity		No information is available.		
STOT -- Single Exposure		No information is available.		
STOT -- Repeated Exposure		No information is available.		
Aspiration Hazard		No information is available.		
Ames test		No information is available.		

STOT = Specific Target Organ Systemic Toxicity

## Section 12: Ecological Information

Toxicity:	LL50 (flathead minnow), 2200 mg/l/96 hour	Stoddard Solvent
	LL50 (rainbow trout) 51 mg/l/96 hours	Stoddard Solvent
Persistence and degradability:	Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment. The volatile components oxidize rapidly by photochemical reactions in air.	Stoddard Solvent
Bioaccumulative potential	No information is available.	
Mobility in soil:	Liquid under most environmental conditions. If it enters soil, it will adsorb to soil particles and will not be mobile. Floats on water. Contains volatile components. Partly evaporates from water or soil surfaces, but a significant proportion will remain after one day	Stoddard Solvent
PBT and vPvB assessment:	PBT/vPvB assessment not available as chemical assessment not required/not conducted	
Other adverse effects:	No information is available.	



## Section 13: Disposal Considerations

**Waste from residues/unused products:** Follow the waste disposal requirements of your country, state, or local authorities.

**RCRA HAZARDOUS WASTE:** This material and containers that are not empty, if discarded, would be regulated as a hazardous waste under RCRA. Treatment and/or disposal must be completed at a RCRA-permitted Treatment, Storage and Disposal Facility (TSD). The storage and transportation of RCRA hazardous wastes are also regulated by the USEPA. Can be incinerated, when in compliance with local regulations.

US EPA Waste Number: D001 (IGNITABLE): When discarded in its purchased form, this material would be regulated under 40 CFR 261.21 as EPA Hazardous Waste Number D001 based on the characteristic of ignitability.

**Contaminated packaging:** Recommend contaminated packaging material should be disposed of as stated above for residues and unused product.

**Rinsate** Do not dispose of rinse water containing product in a sanitary sewer system or storm water drainage system.

## Section 14: Transport Information

### ROAD TRANSPORT:

#### ADR = International Carriage of Dangerous Goods by Road

UN NUMBER:	UN 1866
DOT PROPER SHIPPING NAME	RESIN SOLUTION (CONTAINS Stoddard Solvent)
DOT / ADR HAZARD CLASS:	Flammable
DOT / ADR LABELS:	Class 3
PLACARD:	Flammable, Class 3
DOT / ADR PACKAGING GROUP:	III
HAZARD NUMBER – ADR:	UN1866
ADR PROPER SHIPPING NAME:	RESIN SOLUTION (CONTAINS Stoddard Solvent)

### RAIL TRANSPORT: RID

CLASS No.:	FLAMMABLE
RID PACKING GROUP:	

### SEA TRANSPORT: IMDG

PROPER SHIPPING NAME	FLAMMABLE
UN NUMBER SEA	RESIN SOLUTION (CONTAINS Stoddard Solvent)
CLASS:	UN 1866
PACKING GROUP:	3
EmS No.:	III
MARINE POLLUTANT:	F-E, S-E
SEA TRANSPORT NOTES:	No

### AIR TRANSPORT: IATA/ICAO

UN NUMBER:	UN1866
PROPER SHIPPING NAME	RESIN SOLUTION (CONTAINS Stoddard Solvent)
HAZARD CLASS:	3
PACKAGING GROUP:	III

## Section 15: Regulatory Information

### **TOXIC SUBSTANCES CONTROL ACT (TSCA) STATUS:**

**This product is in compliance with rules, regulations, and orders of TSCA.**

### **SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA) TITLE III SECTION 313 SUPPLIER NOTIFICATION:**

This regulation requires submission of annual reports of toxic chemical(s) that appear in section 313 of the Emergency Planning and Community Right To Know Act of 1986 and 40 CFR 372. This information must be included in all SDS's that are copied and distributed for the material.

The Section 313 toxic chemicals contained in this product are: None



**CALIFORNIA PROPOSITION 65:**

This regulation requires a warning for California Proposition 65 chemical(s) under the statute.  
The California proposition 65 chemical(s) contained in this product are: None

**STATE RIGHT-TO-KNOW TOXIC SUBSTANCE OR HAZARDOUS SUBSTANCE LIST:**

Florida Toxic Substance(s):	Not listed
Massachusetts's hazardous substance(s):	Not listed
Pennsylvania hazardous substance code(s):	Not listed
New Jersey	Not listed
Illinois	Not listed
Michigan	Not listed

**CANADA:**

This SDS will be non-compliant 3 years after the issue date. This SDS contains all of the information required by the Controlled Products Regulations (CPR).

**WHMIS-INFORMATION:**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR), SOR/88-66, Current to February 20, 2012. The classes of controlled products listed in the CPR, Section 32, Part IV, have been reviewed and based on Professional Judgment this product has been determined to be WHMIS controlled as a Combustible liquid: Division 3 of Class B.

**Section 16: Other Information**

Initial issue date:	May 12, 2015
Final revision date:	May 27, 2015
Revision Number:	0
Revision explanation	Initial version
Information Sources:	RTECS, ECHA, REACH, OSHA 29CFR 1910.1200

“Disclaimer: This document is generated to distribute health, safety and environmental data. It is not a specification sheet and none of the displayed data should be construed as a specification. Information on this SDS sheet was obtained from sources which we believe are reliable, and we believe that the information is complete and accurate. However, the information is provided without any warranty, express or implied, regarding its correctness. Some of the information presented and conclusions drawn are from sources other than direct test data of the substance. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may also be beyond our knowledge. It is the user’s responsibility to determine the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. If the product is used as a component in another product, this SDS information may not be applicable. For these reasons, we do not assume any responsibility and expressly disclaim liability for any loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of this product.”

